

WATERBLAST WB12

Dash	ID mm	ID in	OD mm	OD in	WP MPa	WP psi	BP MPa	BP psi	BR mm	BR in	W kg/m	W lb/ft
06	10	3/8	21,4	0,84	900	13.750	2.375	34.375	150	6	0,84	0,56
08	13	1/2	25,4	1,00	900	13.000	2.250	32.500	200	8	1,22	0,82
12	19	3/4	32,0	1,26	900	13.000	2.250	32.500	280	11	1,70	1,14
16	25	1	38,0	1,50	825	12.000	2.060	30.000	355	14	2,26	1,52


WATERBLAST WB15

Dash	ID mm	ID in	OD mm	OD in	WP MPa	WP psi	BP MPa	BP psi	BR mm	BR in	W kg/m	W lb/ft
06	10	3/8	21,4	0,84	1.250	18.000	3125	45.000	150	6	0,85	0,57
08	13	1/2	25,4	1,00	1.100	16.000	2750	40.000	200	8	1,26	0,85
12	19	3/4	31,8	1,25	1.000	14.500	2500	36.250	250	11	1,78	1,20

WATERBLAST FITTINGS


WATERBLAST INSERTS ARE MANUFACTURED USING A SPECIAL STEEL IN ORDER TO ENHANCE THE PERFORMANCE AND RELIABILITY OF THE PRODUCT

A99179 Metric Female 24° cone with O-Ring - Heavy - DIN 3865 DKOS - Slip on nut




Part No.	Hose ID in	Hose ID mm	Dash	Thread mm	C Cut-off mm	CH2 mm
A99179-06-06	3/8	9,5	06	22x1,5	43,5	27,0
A99179-08-06	3/8	9,5	08	24x1,5	42,5	30,0
A99179-06-08	1/2	12,7	08	24x1,5	47,0	30,0
A99179-12-12	3/4	19,0	12	36x2	64,2	46,0
A99179-16-16	1	25,4	16	42x2	73,4	50,0

990170 NPTF Male 60°



Part No.	Hose ID in	Hose ID mm	Dash	Thread in-TPI	Thread Dash	C Cut-off mm	CH1 mm
990170-06-06	3/8	9,5	06	3/8-18	06	40,5	25,0
990170-08-08	1/2	12,7	08	1/2-14	08	42,0	22,0
990170-12-12	3/4	19,0	12	3/4-14	12	44,0	27,0
990170-16-16	1	25,4	16	1-11	16	44,5	36,0

A99001 BSP Female 60°



Part No.	Hose ID in	Hose ID mm	Dash	Thread in-TPI	Thread Dash	C Cut-off mm	CH2 mm
A99001-06-06	3/8	9,5	06	3/8-18	06	22,0	32,0
A99001-08-08	1/2	12,7	08	1/2-14	08	30,0	36,0
A99001-12-12	3/4	19,0	12	3/4-14	12	36,0	37,5



WATERBLAST

Tube: oil and water resistant synthetic rubber
Reinforcement: four high tensile steel spirals
Cover: oil, water and ozone resistant synthetic rubber
Application: very high pressure water jetting
Constant operation: -10°C +70°C
Safety Factor: 2.5:1

